

Z MASTER[®]

5000 SERIES

TORO[®]

PRODUCTIVE FROM TOP TO BOTTOM.



When you cover a lot of ground, you need a machine that keeps up. Toro's Z Master[®] 5000 Series packs the power, fuel efficiency and comfort you demand.

4.4–6.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.



COMFORTABLE RIDE

The deluxe suspension seat features thick cushions, large bolsters and 3-D isolator mounts that absorb bumps and vibrations to reduce operator fatigue.



SMART HOUR METER

Maintain your mower at the proper service intervals. Service reminders, PTO and maintenance (hydro/oil) hours, and battery voltage are easy to read on the large display screen.



EFI FUEL EFFICIENCY

The environmentally friendly design exceeds requirements for CARB Tier III and EPA Phase III, and keeps emissions as low as possible by continuing to run at optimal levels.



HIGH-STRENGTH BLADES

Pick your performance. Match the blade to the job for an outstanding cut everytime.

	72906†		72955 MyRIDE® Suspension System		72910		72930		72911		72951 MyRIDE Suspension System		72918		72912	
POWER SYSTEM																
Commercial Engines at 3600 RPM*	25 hp Kohler® Command PRO EFI (747cc)		25 hp Kohler Command PRO EFI (747cc)		25.5 hp Kawasaki® FX801		25 hp Kohler Command PRO EFI (747cc)		25 hp Kohler Command PRO EFI (747cc)		25 hp Kohler Command PRO EFI (747cc)		▶ 26.5 hp Kohler Command PRO EFI (747cc)		26.5 hp Kohler Command PRO EFI (747cc)	
Starter	Electric		Electric		Electric		Electric		Electric		Electric		Electric		Electric	
Heavy-Duty Canister Air Cleaner	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Drive Tires	23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		▶ 24" x 12" – 12" Tweels® • (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		• 24" x 12" – 12" Tweels® • (61 x 30.5 – 30.5 cm)	
Caster Tires	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	
Fuel/Capacity	Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)		Gas/12-Gal (45.4 L)	
Hour Meter	Smart Hour Meter		Smart Hour Meter		Standard Hour Meter		Smart Hour Meter		Smart Hour Meter		Smart Hour Meter		Smart Hour Meter		Smart Hour Meter	
Hydraulic Drive System	Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors	
Pump	12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)		12cc/rev (shock valves)	
Wheel Motor	14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir	
Maximum Forward Speed	10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)	
Clutch	Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic	
MOWING DECKS																
Deck Size	52" (132.1 cm)		52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		72" (182.9 cm)	
Cutting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE	
Bullnose Bumper	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Adjustable Discharge Baffle	Standard, tools-free		Standard, tools-free		Standard, tools-free		Standard, tools-free		Standard, tools-free		Standard, tools-free		Standard, tools-free		Standard, tools-free	
Rubber Discharge Chute	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Deck Lift Design	Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring	
Spindle Housings	9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum		9" (22.9 cm) Dia. Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Spindle Bearings	Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free	
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)	
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt	
Anti-Scalp Rollers	3 Standard, 1 Optional		▶ 6 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional		▶ 6 Standard, 1 Optional		6 Standard, 1 Optional		6 Standard, 1 Optional	
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	
FEATURES																
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts		▶ MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts		Deluxe Suspension with 3-D Isolation Mounts		Deluxe Suspension with 3-D Isolation Mounts		▶ MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts		Deluxe Suspension with 3-D Isolation Mounts	
Arm Rests	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Seat Suspension System	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Folding ROPS	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Storage Compartment	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Foot Pedal Deck Lift	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Z Stand	Optional		Optional		Optional		Optional		Optional		Optional		Optional		Optional	
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access	
WEIGHTS AND MEASUREMENTS																
Weight	1,168 lbs.	529.8 kg	1,259 lbs.	571 kg	1,216 lbs.	551.6 kg	1,255 lbs.	569.3 cm	1,255 lbs.	569.3 cm	1,304 lbs.	591.5 cm	1,296 lbs.	587.9 kg	1,296 lbs.	587.9 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	53.7"	136.4 cm	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm
Deflector Width	67.6"	171.7 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm
Length	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

†CARB compliant model or model available.