

Z MASTER[®]

7500 SERIES



**TRUSTED COMPANIONS
ARE HARD TO FIND.**

FOR A POWERFUL MOWER THAT'S EASY TO OPERATE, CHECK OUT THE TORO Z MASTER[®] 7500.

Its 96-inch deck (select models) folds up neatly for easy transport, then folds down to handle your biggest jobs in less time than comparable mowers. It delivers all the speed and maneuverability of a zero-turn, along with the superior cut quality you expect from Toro.

POWER THROUGH the toughest mowing jobs with a Yanmar diesel engine or Kohler 38 hp gas engine.

MAXIMIZE PRODUCTIVITY with side and rear discharge commercial cutting decks ranging from 60 to 96 inches.

MOW SMARTER with Horizon[®] Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

RIDE IN COMFORT with the iso-mounted floor pan and deluxe suspension iso-mount seat that dramatically reduce vibration for less operator downtime and more productivity.

TORO[®]



CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20 degrees and down 15 degrees to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



EXTENDED SERVICE INTERVALS

Save on maintenance with extended service intervals and a deck design that uses up to four matching blades. The mower is also backed by a 5-year, 2,000-hour limited warranty (first two years no-hour-limit).



THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.



SUPERIOR PERFORMANCE

Whether you choose a Yanmar diesel engine or a Kohler 38 HP EFI gas engine, your mower is packed with power to tackle the toughest mowing jobs.

	72028[†] Horizon [®] Technology	72029[†] Horizon Technology	72076[†] Horizon Technology	72074[†] Horizon Technology	72096[†] Horizon Technology	74090 Horizon Technology
POWER SYSTEM						
Commercial Engines at 3600 RPM*	25 hp Yanmar [®] Diesel 1267cc	25 hp Yanmar Diesel 1267cc	▶ 37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc	▶ 38 hp Kohler [®] EFI
Heavy-Duty Canister Air Cleaner	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor
Drive Tires	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)	24" x 12" – 12" (61.0 x 30.5 x 30.5 cm)
Caster Tires	15" x 6" – 6" (38.1 x 15.2 x 15.2 cm) Flat-Free Semi-Pneumatic	15" x 6" – 6" (38.1 x 15.2 x 15.2 cm) Flat-Free Semi-Pneumatic	15" x 6" – 6" (38.1 x 15.2 x 15.2 cm) Flat-Free Semi-Pneumatic	15" x 6" – 6" (38.1 x 15.2 x 15.2 cm) Flat-Free Semi-Pneumatic	15" x 6" – 6" (38.1 x 15.2 x 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 x 15.2 cm) Flat-Free Semi-Pneumatic
Fuel/Capacity	Diesel/12.5-Gal (47.3 L)	Diesel/12.5-Gal (47.3 L)	Diesel/12.5-Gal (47.3 L)	Diesel/12.5-Gal (47.3 L)	Diesel/12.5-Gal (47.3 L)	Gasoline/12-Gal (45.4 L)
Hour Meter	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology
Hydraulic Drive System	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki [®] Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	Unitized 16cc Pumps & Wheel Motors w/Cooling Fans
Max Ground Speed (Fwd)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	11.5 mph (18.5 km/h)
Clutch	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Electromagnetic
MOWING DECKS						
Deck Size	60" (152.4 cm) (Rear Discharge)	▶ 72" (182.9 cm) (Rear Discharge)	72" (182.9 cm)	72" (182.9 cm) (Rear Discharge)	▶ 96" (243.8 cm) (Rear Discharge)	96" (243.8 cm) (Rear Discharge)
Cutting Deck	7-Gauge TURBO FORCE [™]	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
Bullnose Bumper	Standard	Standard	Standard	Standard	Standard	Standard
Deck Depth	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)
Adjustable Discharge Baffle	Standard	N/A	Standard	N/A	N/A	N/A
Rubber Discharge Chute	Standard	N/A	Standard	N/A	N/A	N/A
Deck Lift Design	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch
Spindle Housings	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
Cutting Height	1.0" – 5.5" (2.5 – 14.0 cm)	1.0" – 5.5" (2.5 – 14.0 cm)	1.0" – 5.5" (2.5 – 14.0 cm)	1.0" – 5.5" (2.5 – 14.0 cm)	1.0" – 5.5" (2.5 – 14.0 cm)	1.0" – 5.5" (2.5 – 14.0 cm)
Blades	3 blades at 20.5" length	3 blades at 24.5" length	3 blades at 24.5" length	3 blades at 24.5" length	4 blades at 24.5" length	4 blades at 24.5" length
Blade Tip Speed	18,200+ ft/min	18,200+ ft/min	▶ 18,500+ ft/min	18,500+ ft/min	18,100+ ft/min	18,100+ ft/min
Shaft Drive	Standard	Standard	Standard	Standard	Standard	Standard
Anti-Scalp Rollers	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	6 Standard	4 Standard, 2 Side Skids	13 Standard	13 Standard
FEATURES						
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened Deluxe Suspension (Iso-Mount, Flip-Up)
Operator Seat	Standard	Standard	Standard	Standard	Standard	Standard
Arm Rests	Standard	Standard	Standard	Standard	Standard	Standard
Seat Suspension System	Standard	Standard	Standard	Standard	Standard	Standard
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard
Storage Compartment	Standard	Standard	Standard	Standard	Standard	Standard
Z Stand	N/A	N/A	N/A	N/A	N/A	N/A
Floor Pan	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount
WEIGHTS AND MEASUREMENTS						
Weight	1,957 lbs. 887.7 kg	1,964 lbs. 890.9 kg	2,067 lbs. 937.5 kg	2,143 lbs. 972 kg	2,650 lbs. 1,202 kg	2,584 lbs. 1,172 kg
ROPS Height (Folded)	51" 129.5 cm	51" 129.5 cm	51" 129.5 cm	51" 129.5 cm	51" 129.5 cm	51" 129.5 cm
ROPS Height (Upright)	71.8" 182.4 cm	71.8" 182.4 cm	182.4 cm 182.4 cm	71.8" 182.4 cm	71.8" 182.4 cm	71.8" 182.4 cm
Deck Clearance Width	66.3" 186.4 cm	78.3" 198.9 cm	73.6" 186.9 cm	78.3" 198.9 cm	102.3" 259.8 cm	102.3" 259.8 cm
Deflector Width	N/A N/A	N/A N/A	87.6" 222.5 cm	N/A N/A	N/A N/A	N/A N/A
Length	96.48" 245.1 cm	100.68" 255.7 cm	99.68" 245.1 cm	100.68" 255.7 cm	97.38" 247.3 cm	97.38" 247.3 cm

* The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. [†]CARB compliant model or model available.