

# GRANDSTAND®

STAND-ON MOWERS

REVOLUTION™

SEE PAGE 4 FOR NEW BATTERY  
REVOLUTION™ SERIES OPTIONS

# STAND UP TO ANY TERRAIN.



BUMPY PATCHES AND CHALLENGING TERRAIN ARE ALL IN A DAY'S WORK—but feeling them doesn't need to be. GrandStand® combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability. And now the GrandStand is even better with all-new next-generation upgrades that enhance productivity, lower maintenance and make service a breeze.

**IMPROVE PRODUCTIVITY** with easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52" and 60" models—to mow longer with fewer stops.

**GAIN SPEED AND PERFORMANCE** with a new 10 mph max forward ground speed and responsive solid drive linkage. (Select models only.)

**SAVE MAINTENANCE AND TIME** with no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.



## 2.6–5.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



### TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



### CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



### 2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.



### POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.

	74534 79534 CARB Model	74536	72504 71504 CARB Model	72518 <sup>†</sup>	72505 71505 CARB Model	72519	72513	72509								
<b>POWER SYSTEM</b>																
Commercial Engines at 3600 RPM*	15 hp Kawasaki <sup>†</sup> FS (603cc)		▶ 22 hp Kawasaki FX (726cc)	▶ 23 hp Kohler <sup>†</sup> Command PRO <sup>†</sup> EFI (747cc)	22 hp Kawasaki FX (726cc)	▶ 25 hp Kohler Command PRO EFI (747cc)		23.5 hp Kawasaki FX730V (726cc)								
Starter	Electric															
Heavy-Duty Canister Air Cleaner	N/A				▶ Standard											
Drive Tires	18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)	18" x 9.5" – 8" (45.7 x 24.1 – 20.3 cm)		▶ 20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)												
Caster Tires	11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)															
Fuel/Capacity	Gas/7.8-Gal (29.5 L)				Gas/10.5-Gal (39.7 L)											
Digital Hour Meter	Standard															
Hydraulic Drive System	Pumps & Wheel Motors				▶ Unitized Pumps & Wheel Motors											
Pump	10cc/rev															
Wheel Motor	10 cir															
Maximum Forward Speed	8 mph (12.9 km/h)				▶ 10 mph (16.1 km/h)											
Clutch	Electromagnetic															
<b>MOWING DECKS</b>																
Deck Size	36" (91.4 cm)	▶ 40" (101.6 cm)	▶ 48" (121.9 cm)	48" (121.9 cm)	▶ 52" (132.1 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)								
Cutting Deck	7-Gauge TURBO FORCE <sup>†</sup>															
Bullnose Bumper	Standard															
Adjustable Discharge Baffle	Standard															
Rubber Discharge Chute	Standard															
Deck Lift Design	Compression Spring				▶ Extension Spring											
Spindle Housings	Cast Iron				9 3/8" (23.8 cm) Diameter Cast Aluminum											
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard															
Spindle Bearings	Maintenance-Free															
Cutting Height	1.0" – 5.0" (2.5 – 12.7 cm)				▶ 1.5" – 5.0" (3.8 – 12.7 cm)											
Blades	.25" (.6 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel											
Blade Tip Speed					18,500+ ft/min											
Belt Construction	Aramid Fiber V-Belt															
Anti-Scalp Rollers	N/A				▶ Optional		▶ Standard									
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)															
<b>FEATURES</b>																
Steering Controls	Twin Lever															
Operator Platform	Foldable Operator Platform with Suspension															
<b>WEIGHTS AND MEASUREMENTS</b>																
Weight	833 lbs.	377.8 kg	844 lbs.	382.8 kg	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm
Deck Clearance Width	37.6"	95.5 cm	41.8"	106.2 cm	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm	61.5"	156.2 cm
Deflector Width	51.6"	131.1 cm	55.8"	141.7 cm	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm	75.5"	191.8 cm
Length (Platform Up)	61"	154.9 cm	57"	144.8 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm	65"	165.1 cm
Length (Platform Down)	74"	188 cm	70"	177.8 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm	79"	200.7 cm

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

<sup>†</sup>CARB compliant model or model available.

▶ = Step Up Feature