

PROLINE™ SERIES

MID-SIZE MOWERS

TIME SAVER. MONEY MAKER.



Contractors know every second not mowing is a lost opportunity, and training your crew on new equipment can cause unnecessary setbacks in time and money.

MAXIMIZE YOUR EFFICIENCY with the Toro PROLINE mid-size mowers. Not only will your crew be mowing in no time with easy-to-learn controls, but you'll also enjoy top-line reliability and professional cutting performance.

YOU'LL LOVE THE CONVENIENCE of the 2-wheel sulky, which rotates 360° and simply folds away when not in use; no more attaching and removing when trailering! Sold separately.

AND YOU CAN REST EASY knowing that Toro stands behind its mowers with a 3-year, 750-hour warranty.

	44410 44409 CARB Model	44424 44423 CARB Model	44427	44430	44436	44448	44454	44460
POWER SYSTEM								
Commercial Engines at 3600 RPM*	14.5 hp Kawasaki® FS	▶ 15 hp Kawasaki FS	▶ 18.5 hp Kawasaki FS	▶ 22 hp Kawasaki FS	15 hp Kawasaki FX		▶ 22 hp Kawasaki FX	
Starter		Electric					Electric	
Drive Tires	18"		▶ 20"		18"		▶ 20"	
Caster Tires	9"		▶ 11"		9"		▶ 11"	
Fuel/Capacity		Gas / 5 Gal (18.9 L)					Gas / 5 Gal (18.9 L)	
Control System		Twin Lever					Twin Lever	
Transmission		ZT-2800					▶ ZT-3100	
Hour Meter		Standard					Standard	
Maximum Forward Speed		7 mph (11.3 km/h)					7 mph (11.3 km/h)	
Brake System		Integrated Parking Brake					Integrated Parking Brake	

	36" (91.4 cm)	▶ 48" (121.9 cm)	▶ 54" (137.2 cm)	▶ 60" (152.4 cm)	36" (91.4 cm)	▶ 48" (121.9 cm)	▶ 54" (137.2 cm)	▶ 60" (152.4 cm)
MOWING DECKS								
Deck Size	36" (91.4 cm)	▶ 48" (121.9 cm)	▶ 54" (137.2 cm)	▶ 60" (152.4 cm)	36" (91.4 cm)	▶ 48" (121.9 cm)	▶ 54" (137.2 cm)	▶ 60" (152.4 cm)
Cutting Deck		10-Gauge Steel					7/10-Gauge Steel	
Bullnose Bumper		Standard					Standard	
Rubber Discharge Chute		-					▶ Standard	
Deck Lift Assist		Standard					Standard	
Spindle Housings		8" Cast Aluminum					8" Cast Aluminum	
Spindle Bearings		Maintenance-Free					Maintenance-Free	
Cutting Height		1.5" – 4.5" (3.8 – 11.4 cm)					1.5" – 4.5" (3.8 – 11.4 cm)	
Blades		.204" Heat-Treated Steel					.204" Heat-Treated Steel	
Blade Tip Speed		18,500+ ft./min.					18,500+ ft./min.	
Belt Construction		Aramid Fiber V-Belt					Aramid Fiber V-Belt	
Anti-Scalp Rollers		Standard					Standard	

	580 lbs.	263.1 kg	639 lbs.	289.8 kg	648 lbs.	294.9 kg	693 lbs.	314.3 kg	608 lbs.	275.8 kg	669 lbs.	303.5 kg	695 lbs.	315.2 kg	730 lbs.	331.1 kg
WEIGHTS AND MEASUREMENTS																
Weight	580 lbs.	263.1 kg	639 lbs.	289.8 kg	648 lbs.	294.9 kg	693 lbs.	314.3 kg	608 lbs.	275.8 kg	669 lbs.	303.5 kg	695 lbs.	315.2 kg	730 lbs.	331.1 kg
Height	45"	114.3 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm	45"	114.3 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm
Deck Clearance Width	37"	94.0 cm	49"	124.5 cm	55"	139.7 cm	61"	154.9 cm	37"	94.0 cm	49"	124.5 cm	55"	139.7 cm	61"	154.9 cm
Deflector Width	51"	129.5 cm	63"	160.0 cm	69"	175.3 cm	75"	190.5 cm	51"	129.5 cm	63"	160.0 cm	69"	175.3 cm	75"	190.5 cm
Length	77"	195.6 cm	80"	203.2 cm	80"	203.2 cm	83"	210.8 cm	77"	195.6 cm	80"	203.2 cm	80"	203.2 cm	83"	210.8 cm

▶ = Step Up Feature

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

† CARB compliant model or model available.



DRIVE WITH EASE

Shred grass in no time with the easy-to-learn twin-lever controls and drive assist with three settings.



MOWING MUSCLE

Ensure you never lose a job because of broken equipment with a reliable Kawasaki engine that drives .204" blades for a gorgeous, professional cut.



MADE TO LAST

Your Toro is also built to take on years of rough rides with a bullnose bumper and 20" wheels with curb clearance.



QUICK ADJUSTMENT

Changing cut lengths on the go is a snap with a single-point height of cut adjustment.



NO-HASSLE SULKY

The 2-wheel sulky simply folds away, meaning no need to attach and remove it when trailering. Sold separately.