

Z MASTER®

4000 SERIES

REVOLUTION™

SEE PAGE 4 FOR NEW BATTERY
REVOLUTION™ SERIES OPTIONS

BUILT TO DOMINATE. READY TO REIGN.

Show up big, bad, and fearless. The Z Master 4000 is the durability king, providing a royal ride with MyRIDE® suspension system and grass-kicking TURBO FORCE® deck with a bold, dominating look. It's going to cut a path that you know will be noticed.

PRIDE CUT IN EVERY PASS

Constructed with high-strength materials and engineered with proven technologies, the TURBO FORCE cutting deck is built from 100 years of experience and over 100 million unrelenting hours of real-world results.

A BEAST FOR BEAUTY

Every Z Master 4000 is loaded with a heavy-duty front-end design, TURBO FORCE deck with bullnose bumper, and pro-grade engine transforming a battlefield of brutal vegetation into a pristine pro cut.

GET COMFORTABLE CRUSHING IT

Keep mowing full blast in full-time comfort with a deluxe suspension seat. Or get battle-ready with the MyRIDE® Suspension System.



NOW AVAILABLE

**Triple/
DFS bagger**
for HDX PRO XL
models

PERFECT ONE-PASS CUTTING

The TURBO FORCE® Cutting Deck: enhances the after-cut appearance through dual capture anti-scalp rollers, rubber discharge chute, a clear sight-line to rear tires and the offset 7-gauge steel deck.



NO MESSING AROUND

Pairing the durable rugged I-beam front end, along with the TURBO FORCE deck's bullnose bumper and heavy-duty cast aluminum spindle housings, durability is king.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.



MOW ON AND ON

4000s come with conveniences like the optional electronic deck lift assist, to front step thru deck, and USB ports.

4.4–6.6 Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.

	HD		HDX MyRIDE® SUSPENSION SYSTEM		PRO				HDX PRO							
	74050	74054	74052 HDX	74055 HDX	74000	74002	74004	74035	74010 HDX Pro	74015 HDX Pro	74020 HDX Pro XL	74022 HDX Pro XL				
POWER SYSTEM													NEW	NEW		
Commercial Engines at 3600 RPM*	25.5 Kawasaki FX801V (852cc)		▶ 31 hp Kawasaki FX921V (999cc)		24.5 Kawasaki FX751 (852cc)	▶ 25.5 Kawasaki FX801V (852cc)		▶ 26.5 hp Kohler Command Pro EFI (747cc)	▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000 (999cc)					
Starter	Electric		Electric		Electric				Electric							
Heavy-Duty Canister Air Cleaner	Standard		Standard		Standard				Standard							
Drive Tires	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)		24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	▶ 24" x 12" - 12" (61 x 30.5 - 30.5 cm)	▶ Multi Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)					
Caster Tires	15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)		15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)		13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)				13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		▶ 15" x 6.5" - 6" Flat-Free Semi-Pneumatic (38.1 x 16.5 - 15.2 cm)					
Fuel/Capacity	Gas/10-Gal (37.9 L)		Gas/10-Gal (37.9 L)		Gas/10-Gal (37.9 L)				Gas/10-Gal (37.9 L)							
Digital Hour Meter	Standard		Standard		Standard				Standard							
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors		ZT-4400 Integrated Pumps & Wheel Motors		ZT-4400 Integrated Pumps & Wheel Motors				▶ ZT-5400 Integrated Pumps & Wheel Motors							
Maximum Forward Speed	12 mph (19.3 km/h)		12 mph (19.3 km/h)		10 mph (16.1 km/h)				▶ 12 mph (19.3 km/h)							
Clutch	Electromagnetic		Electromagnetic		Electromagnetic				Electromagnetic							
MOWING DECKS																
Deck Size	52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)				
Cutting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE				7-Gauge TURBO FORCE							
Deck Lift Design	Extension Spring		Standard		Extension Spring				Extension Spring							
Spindle Housings	9" (22.9 cm) Dia. Aluminum		9" (22.9 cm) Dia. Aluminum		9" (22.9 cm) Dia. Aluminum				9" (22.9 cm) Dia. Aluminum							
1" (2.5 cm) Spindle Shaft	Standard		Standard		Standard				Standard							
Spindle Bearings	Maintenance-Free		Maintenance-Free		Maintenance-Free				Maintenance-Free							
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)		Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)		Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)				Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)							
Deck Depth	5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)				5.5" (14 cm)							
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel							
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min		18,500+ ft/min				18,500+ ft/min							
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt				Aramid Fiber V-Belt							
FEATURES																
MyRIDE® Suspension System			▶ MyRIDE Suspension System													
Comfort Platform	N/A				N/A				N/A							
Platform Travel	N/A		3.0" (7.62 cm)		N/A				N/A							
Shocks	N/A		1 center / 2 rear		N/A				N/A							
Seat	N/A		High-Back Comfort		N/A				N/A							
Adjustability	N/A		5 Detents, Infinite Adjustability		N/A				N/A							
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened				1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened							
Operator Seat	Deluxe Suspension		High-Back Comfort		Deluxe Suspension				Deluxe Suspension							
LED Lights	Standard		Standard		Optional				Optional							
Step-Through Floorpan	Standard		N/A		▶ Standard				Standard							
Electric Deck Lift Assist	Optional		▶ Standard		Optional				Optional							
Smart Hour Meter & USB	Standard		Standard		Standard				Standard							
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit		5-Year 1250-Hour 2-Year No Hour Limit		5-Year 1250-Hour 2-Year No Hour Limit				▶ 5-Year 1500-Hour 2-Year No Hour Limit							
WEIGHTS AND MEASUREMENTS																
Weight	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,360 lbs.	616.9 kg	1,300 lbs.	589.7 kg
Deck Clearance Width	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	53.7"	136.4 cm	61.7"	156.7 cm	65.5"	166.4 cm	75.6"	192.0 cm
Deflector Width	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.3"	191.3 cm	87.6"	222.5 cm
Length	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	89.3"	226.8 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

▶ = Step Up Feature