

Z MASTER®

6000 SERIES

OWN THE MOWER THAT OWNS EVERY JOB.



The Z Master® 6000 Series is one of our most advanced and most comfortable zero turn mowers.

6.3–7.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.

MyRIDE® SUSPENSION SYSTEM



The MyRIDE Suspension System features a rear shock adjustable operator platform that isolates bumps and vibrations.

Models 72967 and 72968 only. See pages 6–7 for details.



HORIZON® TECHNOLOGY

Choose the performance mode to increase productivity and reduce fuel consumption.

Models 72969, 72946 and 72947 only.
See page 8 for details.



PRO RESULTS EVERY TIME

TURBO FORCE® 5.5" deep cutting decks feature 18,500+ ft./min. blade tip speed and nearly 1/4" thick heat-treated steel blades.



DECK LIFT ASSIST

Standard deck lift assist foot pedal allows operator to adjust the deck height quickly and easily.

				MyRIDE [®] SUSPENSION SYSTEM	HORIZON [®] TECHNOLOGY				MyRIDE [®] SUSPENSION SYSTEM	HORIZON [®] TECHNOLOGY													
	72926	72960	72965	72967	72946	72928	72961	72968	72947	72980	72982												
POWER SYSTEM	NEW												NEW										
Commercial Engines at 3600 RPM*	26.5 hp Kohler [®] Command PRO EFI (747cc)		▶ 31 hp Kawasaki [®] FX (999cc)			▶ 38 hp Kohler Command PRO EFI (999cc)		26.5 hp Kohler Command PRO EFI (747cc)		31 hp Kawasaki FX (999cc)		▶ 38 hp Kohler Command PRO EFI (999cc)		▶ 37 hp Vanguard w/Oil Guard (993cc)									
Electric Start	Standard																						
Heavy-Duty Canister Air Cleaner	Standard																						
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)			▶ 24" x 12" – 12" Michelin [®] Tweels (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)																	
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)																						
Fuel/Capacity	Gas/12-Gal (45.4 L)																						
Hour Meter	Smart Hour Meter		Standard			▶ Horizon Technology		Smart Hour Meter		Standard		▶ Horizon Technology		Standard									
Hydraulic Drive System	Unitized Pumps & Wheel Motors																						
Pump	16cc/rev																						
Wheel Motor	17.1 cir																						
Maximum Forward Speed	11.5 mph (18.5 km/h)										▶ 12 mph (19.3 km/h)												
Clutch	Electromagnetic																						
MOWING DECKS																							
Deck Size	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)		72" (182.9 cm)	72" (182.9 cm)	72" (182.9 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)											
Cutting Deck	7-Gauge TURBO FORCE [®]																						
Bullnose Bumper	Standard																						
Adjustable Discharge Baffle	Standard, Tools-Free																						
Rubber Discharge Chute	Standard																						
Deck Lift Design	Extension Spring																						
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum																						
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard																						
Spindle Bearings	Maintenance-Free																						
Cutting Height	1.0" – 5.5" (2.5 cm – 14 cm)																						
Blades	.204" (.5 cm) Heat-Treated Steel																						
Blade Tip Speed	18,500+ ft/min																						
Belt Construction	Aramid Fiber V-Belt																						
Anti-Scalp Rollers	4 Standard, 1 Optional					▶ 6 Standard, 1 Optional					4 Standard, 1 Optional ▶ 6 Standard, 1 Optional												
Carrier Frame Construction	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)																						
FEATURES																							
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened																						
Operator Seat	Deluxe Suspension w/ 3-D Isolation Mounts			▶ MyRIDE Suspension System		Deluxe Suspension w/ 3-D Isolation Mounts					▶ MyRIDE Suspension System		Deluxe Suspension w/ 3-D Isolation Mounts										
Armrests	Standard																						
Seat Suspension System	Standard																						
Folding ROPS	Standard																						
Storage Compartment	Standard																						
Foot Pedal Deck Lift	Standard																						
Z Stand	Optional																						
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access																						
WEIGHTS AND MEASUREMENTS																							
Weight	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,370 lbs.	621.4 kg	1,289 lbs.	584.7 kg	1,350 lbs.	612.3 kg	1,334 lbs.	605.1 kg	1,440 lbs.	653.2 kg	1,369 lbs.	621 kg	1,447 lbs.	656 kg	1,644 lbs.	746 kg	
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	
Deck Clearance Width	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	61.7"	156.7 cm	73.6"	186.9 cm	
Deflector Width	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	87.6"	222.5 cm	87.6"	222-.5 cm	87.6"	222-5 cm	87.6"	222.5 cm	75.7"	192.3 cm	87.6"	222.5 cm	
Length	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	83.1"	211.1 cm	86.1"	218.7 cm	

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature