

Z MASTER®

7500 SERIES

NEW

**MASSIVE
144-INCH
WING-DECK**



STEP UP YOUR PRODUCTIVITY WITH THE TORO Z MASTER® 7500-D. The NEW 144-inch deck folds up neatly to only 83" for fast and easy transport up to 17 MPH, then folds down to handle your biggest jobs in less time than comparable mowers. Powerful engines deliver all the speed and maneuverability of a zero-turn, along with the superior cut quality you expect from Toro.

POWER THROUGH the toughest mowing jobs with a Yanmar diesel engine or Kohler 38 hp gas engine.

MAXIMIZE PRODUCTIVITY with side and rear discharge commercial cutting decks ranging from 60 to 144 inches.

MOW SMARTER with Horizon® Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

RIDE IN COMFORT with the iso-mounted floor pan and deluxe suspension iso-mount seat that dramatically reduce vibration for less operator downtime and more productivity.

MASSIVE 144-INCH WINGSPAN REDEFINES THE PRODUCTIVE WORKHORSE



CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20° and down 15° to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.



EXTENDED SERVICE INTERVALS Save on maintenance with extended service intervals and a deck design that uses up to four matching blades. The mower is also backed by a 5-year, 1,500-hour limited warranty (*first two years no-hour-limit*).



SUPERIOR PERFORMANCE

Whether you choose a Yanmar diesel engine or a Kohler 38 HP EFI engine, your mower is packed with power to tackle the toughest mowing jobs.

	HORIZON™ TECHNOLOGY														HORIZON™ TECHNOLOGY W/ORACLE					
	72028†		72029†		72027		72030		72076†		72074†		72098†		74090		72144			
																		NEW		
POWER SYSTEM																				
Commercial Engines at 3600 RPM*	25 hp Yanmar Diesel 1267cc						▶ 37 hp Yanmar Diesel 1642cc						▶ 38 hp Kohler® EFI				▶ 44 hp Yanmar Diesel 1568cc			
Heavy-Duty Canister Air Cleaner	Air Filtration System with Electronic Vacuum Sensor																			
Drive Tires	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)												24" x 12" – 12" (61.0 x 30.5 x 30.5 cm)		▶ 26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)					
Caster Tires	15" x 6" – 6" Flat-Free Semi-Pneumatic (38.1 x 15.2 x 15.2 cm)												13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 x 15.2 cm)		▶ 15" x 6" – 6" Flat-Free Semi-Pneumatic (38.1 x 15.2 x 15.2 cm)					
Fuel/Capacity	Diesel/12.5-Gal (47.3 L)						Gasoline/12-Gal (45.4 L)						Diesel/12.5-Gal (47.3 L)							
Hour Meter	Horizon Technology																			
Hydraulic Drive System	17.84 cu in Hydro-Gear HGM-H Motors with 18cc Kanzaki® Pump												Unitized 16cc Pumps & Wheel Motors w/Cooling Fans		17.84 cu in Hydro-Gear HGM-H Motors with 18cc Kanzaki Pump					
Max Ground Speed (Fwd)	12.5 mph (20.1 km/h)												11.5 mph (18.5 km/h)		10/17 mph (16.1/27.4 km/h)					
Clutch	Wet Disc												Electromagnetic		Wet Disc					
MOWING DECKS																				
Deck Size	60" (152.4 cm) (Rear Discharge)		▶ 72" (182.9 cm) (Rear Discharge)		60" (152.4 cm)		72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm) (Rear Discharge)		▶ 96" (243.8 cm) (Rear Discharge)		96" (243.8 cm) (Rear Discharge)		▶ 144" (365.7 cm) (Rear Discharge)			
Cutting Deck	7-Gauge TURBO FORCE™																			
Bullnose Bumper	Standard																			
Deck Depth	5.5" (14.0 cm)																			
Adjustable Discharge Baffle	N/A						Standard						N/A							
Rubber Discharge Chute	N/A						Standard						N/A							
Deck Lift Design	Hydraulic with Rocker Switch																			
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum																			
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard																			
Spindle Bearings	Maintenance-Free																			
Cutting Height	1.0" – 5.5" (2.5 – 14.0 cm)																			
Blades	3 blades at 20.5" length												4 blades at 24.5" length				▶ 6 blades at 24.5" length			
Blade Tip Speed	18,200+ ft/min						▶ 18,500+ ft/min						18,100+ ft/min				18,500+ ft/min			
Shaft Drive	Standard																			
Anti-Scalp Rollers	4 Standard, 2 Side Skids						6 Standard						4 Standard, 2 Side Skids		13 Standard		13 Standard		13 Standard	
FEATURES																				
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened																			
Operator Seat	Deluxe Suspension (Iso-Mount, Flip-Up)																			
Armrests	Standard																			
Seat Suspension System	Standard																			
Folding ROPS	Standard																			
Cooling Fans	N/A												▶ Standard							
Storage Compartment	Standard																			
Floor Pan	Flip-Up, Iso-Mount																			
WEIGHTS AND MEASUREMENTS																				
Weight	1,957 lbs.	887.7 kg	1,964 lbs.	890.9 kg	1,987 lbs.	901.3 kg	2,047 lbs.	928.5 kg	2,067 lbs.	937.5 kg	2,143 lbs.	972 kg	2,650 lbs.	1,202 kg	2,584 lbs.	1,172 kg	3,270 lbs.	1,483 kg		
ROPS Height (Folded)	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm		
ROPS Height (Upright)	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm		
Deck Width	66.3"	186.4 cm	78.3"	198.9 cm	61.4"	156.0 cm	73.4"	186.4 cm	73.6"	186.9 cm	78.3"	198.9 cm	102.3"	259.8 cm	102.3"	259.8 cm	144.9"	368.1 cm		
Deck Width – Wings Up	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	73"	185.4 cm	73"	185.4 cm	83"	210.8 cm		
Deflector Width	N/A	N/A	N/A	N/A	72.8"	184.9 cm	84.9"	215.6 cm	87.6"	222.5 cm	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
Length	96.48"	245.1 cm	100.68"	255.7 cm	99.68"	245.1 cm	99.6"	253.0 cm	99.68"	245.1 cm	100.68"	255.7 cm	97.38"	247.3 cm	97.38"	247.3 cm	101.3"	257.3 cm		

*The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. †CARB compliant model or model available.

▶ = Step Up Feature