

COMMERCIAL 2000 SERIES	Z MASTER® COMMERCIAL 2000 SERIES		
	74141	74143	74145
ENGINE* AT 3600 RPM	20.5 hp Kawasaki® FX 726cc	22 hp Kawasaki FX 726cc	23.5 hp Kawasaki FX 726cc
ELECTRIC START	Standard		
HEAVY-DUTY CANISTER AIR CLEANER	Standard		
DRIVE TIRES	22" x 9.5" - 12"	23" x 9.5" - 12"	23" x 10.5" - 12"
CASTER TIRES	13" x 5" - 6" Pneumatic	13" x 6.5" - 6" Pneumatic	
FUEL CAPACITY	8 gallons		
FUEL GAUGE	Standard		
DIGITAL HOUR METER	Standard		
HYDRAULIC DRIVE SYSTEM	ZT-3400, 12 cc pumps		
MAX GROUND SPEED (FWD)	8.5 mph		
SEAT	Custom Two-Toned		
DECK WIDTH	48"	52"	60"
CUTTING DECK	TURBO FORCE®		
DECK DEPTH	5.0"		
DECK CONSTRUCTION	7/10-gauge high-strength steel		
BULL-NOSE BUMPER	Standard		
RUBBER DISCHARGE CHUTE	Standard		
DECK SPINDLES	8" Alum   Sealed ball bearings   1" Shaft		
DECK LIFT ASSIST PEDAL	Standard		
CUTTING HEIGHT	1.5" - 5.0" in .25" increments	1.5" - 5.5" in .25" increments	



#### COMMERCIAL ENGINES

Powerful and reliable commercial-grade Kawasaki FX engines provide professional-quality and performance. Heavy-duty canister air filtration system protects engine from contaminants and prolongs product life.



#### TOUGH SPINDLE ASSEMBLIES

Toro's rugged 8" aluminum spindle assemblies survive impacts that would destroy lesser spindles.



#### OPERATOR COMFORT

The custom, bolstered seat and adjustable armrests ensure operator comfort and reduce fatigue, and the standard lift assist pedal allows for fast and easy deck height adjustments.