

## PROFESSIONAL 5000 SERIES

REAR  
DISCHARGE

## Z MASTER® PROFESSIONAL 5000 SERIES WITH REAR DISCHARGE DECKS

74942

74944

ENGINE\* AT 3600 RPM

25 hp Kohler  
Command Pro EFI 747cc26.5 hp Kohler  
Command Pro EFI 747cc

ELECTRIC START

Standard

HEAVY-DUTY CANISTER AIR CLEANER

Standard

DRIVE TIRES

24" x 12" x 12"

CASTER TIRES

13" x 6.5" - 6" Flat-free semi-pneumatic

FUEL CAPACITY

12 gallons, single-point fill

DIGITAL FUEL GAUGE

Standard

DIGITAL HOUR METER

Standard

HYDRAULIC DRIVE SYSTEM

Unitized 12 cc pumps and wheel motors

MAX GROUND SPEED (FWD)

10 mph

SEAT

Deluxe suspension seat with 3-D isolation mounts for maximum comfort

DECK WIDTH

60"

72"

CUTTING DECK

TURBO FORCE® Rear Discharge

DECK DEPTH

5.5"

DECK CONSTRUCTION

7-gauge high-strength steel

BULL-NOSE BUMPER

Standard

ADJUSTABLE DISCHARGE BAFFLE

Standard

RUBBER DISCHARGE CHUTE

Standard

1" HEAVY-DUTY SPINDLE SHAFT

Standard

SPINDLE BEARINGS

Greaseable Ball Bearings

DECK LIFT ASSIST PEDAL

Standard

CUTTING HEIGHT

1.0" - 5.5" in .25" increments



## MORE ADVANTAGES

Two blades rotate clockwise and one rotates counter-clockwise allowing for even distribution of clippings.



## DUAL TRIMMING

Trim around trees and landscaping obstacles with either side of the deck. Durable, adjustable side bumpers act as an anti-scalp system.



## RUGGED PERFORMANCE

Highly productive in taller grass and weed conditions.

TORO

490-9339 ©2016 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \*The gross horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. \*\*See retailer for warranty details.