
| PROFESSIONAL 7000 SERIES DIESEL | Z MASTER® PROFESSIONAL 7000 SERIES DIESEL | | |
|----------------------------------|---|----------|-----------|
| | 74266 | 74267 | 74274 |
| ENGINE* AT 3600 RPM | 25 hp Kubota® Diesel 898cc | | |
| ELECTRIC START | Standard | | |
| HEAVY-DUTY CANISTER AIR CLEANER | | Standard | |
| DRIVE TIRES | 23" x 9.5"- 12" | 24" x 1 | 12" - 12" |
| CASTER TIRES | 13" x 6.5" - 6" Flat-free semi-pneumatic | | |
| FUEL CAPACITY | 12 gallons | | |
| FUEL GAUGE | Standard | | |
| DIGITAL HOUR METER | Standard | | |
| HYDRAULIC DRIVE SYSTEM | Hydro-Gear with system check relief and oil cooler 16cc/rev pumps and 18.9 cir wheel motor with 1 1/4" tapered shaft | | |
| MAX GROUND SPEED (FWD) | 11.2 mph | | |
| SEAT | Deluxe Suspension Seat for maximum comfort | | |
| DECK WIDTH | 52" | 60" | 72" |
| CUTTING DECK | TURBO FORCE* | | |
| DECK DEPTH | 5.5" | | |
| DECK CONSTRUCTION | 7-gauge high-strength steel | | |
| BULL-NOSE BUMPER | Standard | | |
| ADJUSTABLE DISCHARGE BAFFLE | Standard, no tools | | |
| RUBBER DISCHARGE CHUTE | Standard | | |
| SPINDLE HOUSINGS | 9" diameter cast iron | | |
| SPINDLE SHAFT/BEARINGS | 1" shaft/greasable | | |
| DECK LIFT ASSIST PEDAL | Standard | | |
| CUTTING HEIGHT | 1.5" - 5.0" in .25" increments | | |



HIGH TORQUE AND LONGER RUN TIME

While gas powered mowers lose torque under heavy conditions, the diesel engine increases torque to lug through demanding turf and eliminate stalling.



TOUGH SPINDLE ASSEMBLIES

Toro's rugged cast-iron spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.



COMFORTABLE RIDE

The deluxe suspension seat features thick cushions and large bolsters that absorb bumps and vibrations to reduce operator fatigue.

