

Toro's pressure-compensating 1/2" threaded Drip Bubblers are built to perform in tough environments. Bringing commercial-grade ruggedness to drip irrigation, they're easy to install, virtually maintenance-free, and are a more robust alternative to traditional drip emitters connected to 1/4" tubing. The innovative design of these Drip Bubblers combines the low flow rates of drip emitters with the ease of 1/2" PVC riser installation.

FEATURES & BENEFITS

Easy to Install

Easily threads on to a 1/2" threaded riser. The self-sealing screen eliminates the cost and labor of having to use plumber's tape on every riser.

Easy to Maintain

Self-cleaning mechanism flushes at every startup, ensuring reliable operation and fewer maintenance headaches.

Durable Construction

Commercial-grade plastic and chloramine-stabilized silicone diaphragm provide dependable UV- and chemical-resistant performance in the least forgiving of environments.

DRIP BUBBLERS MODEL LIST

Model	Description
DB-04-PC	4 GPH PC Drip Bubbler (0.067 gpm)
DB-09-PC	9 GPH PC Drip Bubbler (0.15 gpm)
DB-15-PC	15 GPH PC Drip Bubbler (0.25 gpm)
DB-30-PC	30 GPH PC Drip Bubbler (0.5 gpm)
DB-04-PC-E	4 GPH PC Drip Bubbler, Effluent (0.067 gpm)
DB-09-PC-E	9 GPH PC Drip Bubbler, Effluent (0.15 gpm)
DB-15-PC-E	15 GPH PC Drip Bubbler, Effluent (0.25 gpm)
DB-30-PC-E	30 GPH PC Drip Bubbler, Effluent (0.5 gpm)
DSB-04-PC	4 GPH PC Drip Stream Bubbler (0.067 gpm)
DSB-08-PC	8 GPH PC Drip Stream Bubbler (0.13 gpm)
DSB-04-PC-E	4 GPH PC Drip Stream Bubbler, Effluent (0.067 gpm)
DSB-08-PC-E	8 GPH PC Drip Stream Bubbler, Effluent (0.13 gpm)



Drip Stream Bubbler



Drip Bubbler

SPECIFICATIONS

Operational

- Pressure Compensation: 20 – 60 psi
- Recommended operating pressure: 30 psi
- Minimum Filtration Requirement: 80 Mesh
- 1/2" FIPT inlet; diffuser cap outlet
- Self-sealing screen eliminates need for plumber's tape
- Self-cleaning flush at startup minimizes clogging and maintenance
- Flow rate molded onto the bubbler for easy identification
- Commercial-grade plastic and chloramine-stabilized silicone diaphragm provide dependable UV- and chemical-resistant performance
- Effluent and non-effluent models
- Installation of pressure-regulating drip zone kit recommended for optimal performance
- Drip Stream Bubbler models feature a unique four-outlet configuration with removable caps to ensure water does not trickle straight down to the PVC riser base if mounted vertically

Warranty

- Two years