



FEATURES & BENEFITS

Available as Stake Assembly or as Barbed Emitter

Varistake connects to 1/4" micro-tube (T-EHD0437) for precise placement at plant. Varis emitter installs directly onto drip lateral.

Adjustable Flow Rate

Allows for ease of installation even to the smallest of areas.

Easy To Maintain

Green top unthreads completely to permit easy inspection and cleaning.

VARIS AND VARISTAKE ADJUSTABLE EMMITERS MODEL LIST

Diameter of Throw (maximum opening at 30 clicks):		
psi	AT 1" HEIGHT	AT 2.5" HEIGHT
20	6"	8"
30	13 1/2"	15 1/2"
40	21"	27"

Varis and Varistake Flows:	
psi	FLOW RANGE
10	0-7 gph
20	0-10 gph
30	0-11 gph
40	0-14 gph

Specifying Information—Varis and Varistake Emitters

Model	Description
T-DAK05	Varis Adjustable Emitter with 1/4" Barbed Inlet
T-DAK15	Varistake Adjustable Emitter with 4 3/4" Stake and 1/4" Barbed Inlet



Specifying Information—PC Regulators

Model	Description
T-PMR15-LF	3/4", 15 psi, 1/10-8 gpm Low Flow Pressure Regulator
T-PMR25-LF	3/4", 25 psi, 1/10-8 gpm Low Flow Pressure Regulator
T-PMR40-MF	3/4", 40 psi, 2-20 gpm Medium Flow Pressure Regulator
T-PR25-HF	1 1/4" x 1", 25 psi, 10 - 32 gpm, High Flow Pressure Regulator
T-PMR25-MF	3/4", 25 psi, 2 - 20 gpm, Medium Flow Pressure Regulator