

TURF RENOVATION

SPRAYMASTER®

NEW



Uneven applications cost you valuable time and money, not to mention unhappy clients. Eliminate the need for a manual pressure regulator and get precise liquid and granular spreads with Toro's Dual Smart Hour Meters on the lean-to-steer model. Check your fluid levels with just a glance with new white tanks. SprayMaster is designed to work seamlessly on any sized property.

| | SPRAYMASTER MAX | SPRAYMASTER MAX XL | SPRAYMASTER INTERMEDIATE | SPRAYMASTER 36" |
|--------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| | 34237 | 34235 | 34233 | 34231 |
| POWER AND DRIVE SYSTEM | | | | |
| Engine* | Vanguard Commercial 16 hp |
| Engine Orientation | Horizontal | Horizontal | Horizontal | Vertical |
| Fuel Capacity | Gas/5.0 Gal (18.9 L) |
| Electric Start | Yes | Yes | Yes | Yes |
| Transmission | Pump and Wheel Motor |
| Maximum Forward Speed | 8 mph | 8 mph | 8 mph | 7 mph |
| SPREADER SYSTEM | | | | |
| Hopper Size | 220 lbs | 220 lbs | 220 lbs | 120 lbs |
| Fertilizer Capacity | 320 lbs | 320 lbs | 320 lbs | 220 lbs |
| Spread Width | Adjustable from 3'-25' | Adjustable from 3'-25' | Adjustable from 3'-25' | Adjustable from 3'-25' |
| Deflector Shield | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel |
| Spinner Motor | Hydraulic | Hydraulic | Hydraulic | Hydraulic |
| SPRAY SYSTEM | | | | |
| Pump Capacity | 5 GPM | 7 GPM | 5 GPM | 5 GPM |
| Spray Capacity | 60 Gal (2-30 Gal Tanks) | 60 Gal (2-30 Gal Tanks) | 30 Gal (2-15 Gal Tanks) | 24 Gal (2-12-Gal Tanks) |
| Spray Width | 2 ft, 6 ft, 8 ft, or 10 ft | 2 ft, 6 ft, 8 ft, or 10 ft | 2 ft, 4 ft, 6 ft, or 8 ft | 2 ft, 4 ft, 6 ft, or 8 ft |
| Three Section Breakaway Boom | Standard with 5 Spray nozzles | Standard with 5 Spray nozzles | Standard with 4 Spray nozzles | Standard with 4 Spray nozzles |
| Spot Spray Hose | 75 ft Hose Reel | 75 ft Hose Reel | 75 ft Hose Reel | 15 ft Coil Hose |
| WEIGHT AND MEASUREMENTS | | | | |
| Weight | 992 lbs. (450.0 kg) | 995 lbs. (451.3 kg) | 920 lbs. (417.3 kg) | 725 lbs. (328.9 kg) |
| Height | 50" (127.0 cm) | 50" (127.0 cm) | 50" (127.0 cm) | 50" (127.0 cm) |
| Width | 52" (132.1 cm) | 52" (132.1 cm) | 46" (116.8 cm) | 35.5" (90.2 cm) |
| Length | 73" (185.4 cm) | 73" (185.4 cm) | 73" (185.4 cm) | 73" (185.4 cm) |

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.



MAXIMUM OF
4.0 Acres
COVERED PER HOUR



EASY FLUID CHECK.
Check your fluid levels with just a glance with new white tanks.



CLOG-FREE FLOW.
Enjoy clog-free, consistent liquid flows with an auxiliary pump that delivers 2 gal./min. and up to 10 PSI.



SIMPLIFIED STEERING.
Make adjustments on the fly with one hand with control forward/reverse and left/right steering.

