



## TEMPUS PRO



- From 4 to 16 Stations with expanding module of 4 st. each
- Indoor/Outdoor
- Armchair programming

MODULAR SOLUTION



Learn more at  
**toro.com**



### Features & Benefits

**IOT Wi-Fi ready (Wi-Fi module optional)\***

#### Scheduling Flexibility

4 independent programs and 6 start times per program

**Same programming module fits all versions**

?????????

**Same programming path**

???????????????

**No battery**

### PROGRAMMING MODULE + BACK PART MODULE



1 programming module

1 Back part Module  
(with terminal block)

TEMPUS  
Controller

\*With Wi-Fi module the controller can be accessed anywhere via Wi-Fi from a Smartphone

## Specifications

### Dimensions

- 186 mm W x 140 mm H x 67mm D
- Weight: 1,5 kg

### Electrical Specifications

- Input power:
  - 220 VAC, 50Hz
- Output power:
  - Max per station: 24 VAC (0,25 A)
  - Max total (including MV control): 24 VAC (0,325 A)
- Operating temperature: from -10° to 60° C

### Operating Specifications

- 4 independent programs, (one can be set up as loop program)
- 6 start times per program
- Watering time: from 1 min to 8 hours (1 min increase)
- Possibility to work in m:h or s:m (up to 8 min)
- Flexible irrigation programming
  - Daily (6 start times per day)
  - Weekly
  - Irrigation on even and odd days
  - Irrigation at 1 to 30 day intervals
- Rain delay programmable up to 31 days
- Water Budget from 0% to 200% or pre-set option
- Stacking Program
- Automatic, semi-automatic and manual start
- Test program for all the stations
- Permanent memory
- The "Super Cap" option provides back up power for maintaining the current time and date in the event of a power cut for more than 24 hours (without needing batteries)
- Rain sensor activation through switch
- Programmable rain delay between stations (from 1 sec to 8 min)
- Pulse sensor input
- Pulse sensor may be active when no valve is working
- Sensors may be managed in 5 different modes (Off, start, stop, skip, hold)
- Electronical or mechanical program retention possibility
- Electrical test capability
- Help button (programming only)
- Multilingual display

### Optional Accessories

- IOT Wi-Fi module
- Expanding module 4 stations

### Warranty

- 2 years

### TEMPUS PRO Assembled Series Model List

Model	Description
TEMP-P	4-stations, Indoor, 220 VAC
TEMP-P-EXT	4-stations, Outdoor, 220 VAC
TEMP-P-SM	Station expanding module 4 stations

### TEMPUS PRO Modular Series Model List

Model	Description
TEMP-MOD	Programming module
TEMP-P-B	4-stations, Indoor, back part+transformer, 220 VAC
TEMP-P-B-EXT	4-stations, Outdoor, back part+transformer, 220 VAC
TEMP-P-SM	Station expanding module 4 stations

### Accessories

Model	Description
TEMP-P-WF	Wi-Fi module for Tempus Pro

### Specifying Information— TEMPUS PRO Assembled Series

TEMP-P-XXX	
Model	Cabinet Type
TEMP-P	XXX
TEMP - Tempus Pro Controller 4 station	EXT—Outdoor

### Specifying Information—TEMPUS PRO Modular Series

TEMP-XXX			TEMP-P-X-XXX				TEMP-P-XX	
Model	Part		Model	Parts	Cabinet Type		Model	Parts
TEMP	XXX		TEMP-P	X	XXX		TEMP-P	XX
TEMP - Tempus Controller	MOD - Programming Module	+	TEMP - Tempus PRO Controller 4 stations	B - Back Part + transformer	EXT - Outdoor	+	TEMP - Tempus PRO Controller	SM - Station expanding module 4 stations

Example: a 8 station Tempus controller in an outdoor cabinet would be specified as: TEMP-MOD + TEMP-B-EXT + TEMP-P-SM

### toro.com

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801  
Fax: (1) 952 887 8258

Printed in U.S.A.  
©2016 The Toro Company.  
All Rights Reserved.  
GB 200-XXXXNA Electronic file only.



facebook.com  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope



Count on it.