

UNIQUE

LIGHTING SYSTEMS®

IES FLOOD REPORT

PHOTOMETRIC FILENAME : COMT-12-L527.IES


DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 3321
[TESTLAB] Labsphere
[ISSUEDATE] 8/15/2019 3:00:00 PM
[MANUFAC] TORO
[LUMINAIRE] COMT-12-L527
[LAMP] LED-5W-CM6FL27K
[POWERFACTOR] 0.9176
[ATHD] 0.00%
[CURRENT] 0.43
[VOLTAGE] 12.00
[Lumens] 304.68
[END VOLTS] 12.01
[END CURRENT] 0.43
[END POWER] 4.68

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS

NEMA Type	5 H x 5 V
Maximum Candela	405.84
Maximum Candela Angle	0H 5V
Horizontal Beam Angle (50%)	48.2
Vertical Beam Angle (50%)	55.7
Horizontal Field Angle (10%)	78.1
Vertical Field Angle (10%)	94.8
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	182
Beam Efficiency	N.A.
Field Lumens	286
Field Efficiency	N.A.
Spill Lumens	20
Luminaire Lumens	306
Total Efficiency	N.A.
Total Luminaire Watts	4.77
Ballast Factor	1.00




IES FLOOD REPORT
PHOTOMETRIC FILENAME : COMT-12-L527.IES

AXIAL CANDELA


DEG.	HOR.	DEG.	VERT.
90	.11	90	.56
85	.09	85	1.27
75	.12	75	4.81
65	.09	65	11.99
55	.1	55	32.17
47.5	4	47.5	65.22
42.5	20	42.5	97.95
37.5	44.43	37.5	139.79
33	81.53	33	184.17
29	132.17	29	226.83
25.5	178.99	25.5	263.91
22.5	220.64	22.5	292.37
19.5	262.42	19.5	319.53
17	296.58	17	339.54
15	323.9	15	355.54
13	339.4	13	368.06
11	354.91	11	380.58
9	367.57	9	390.64
7	377.38	7	398.24
5	387.2	5	405.84
3	392.08	3	403.26
1	396.95	1	400.68
0	399.39	0	399.39
-1	396.95	-1	397.91
-3	392.08	-3	394.94
-5	387.2	-5	391.97
-7	377.38	-7	379.59
-9	367.57	-9	367.21
-11	354.91	-11	353.41
-13	339.4	-13	338.18
-15	323.9	-15	322.96
-17	296.58	-17	303.6
-19.5	262.42	-19.5	279.4
-22.5	220.64	-22.5	233.94
-25.5	178.99	-25.5	186.76
-29	132.17	-29	140.92
-33	81.53	-33	105.59
-37.5	44.43	-37.5	71.19
-42.5	20	-42.5	35.16
-47.5	4	-47.5	13.17
-55	.1	-55	1.87
-65	.09	-65	.09
-75	.12	-75	.1
-85	.09	-85	.12
-90	.11	-90	.11

AXIAL CANDELA DISPLAY




Maximum Candela = 405.84 Located At Horizontal Angle = 0, Vertical Angle = 5
Horizontal Axial Candela

AXIAL CANDELA DISPLAY



Maximum Candela = 405.84 Located At Horizontal Angle = 0, Vertical Angle = 5
Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 405.84 Located At Horizontal Angle = 0, Vertical Angle = 5
50% Maximum Candela = 202.92
10% Maximum Candela = 40.584