

UNIQUE

LIGHTING SYSTEMS®

IES FLOOD REPORT

PHOTOMETRIC FILENAME : COMH-12-L830.IES


DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 3325
[TESTLAB] Labsphere
[ISSUEDATE] 8/20/2019 6:22:33 AM
[MANUFAC] TORO
[LUMINAIRE] COMH-12-L830
[LAMP] LED-8W-CM6FL30K
[_AMBIENT] 21.5 deg C
[_POWERFACTOR] 0.9206
[_ATHD] 0.00%
[_CURRENT] 0.75
[_VOLTAGE] 11.98
[_Lumens] 729.33
[_END VOLTS] 12.00
[_END CURRENT] 0.72
[_END POWER] 7.89

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS

NEMA Type	4 H x 4 V
Maximum Candela	1735.73
Maximum Candela Angle	0H -5V
Horizontal Beam Angle (50%)	35.4
Vertical Beam Angle (50%)	36.6
Horizontal Field Angle (10%)	61.5
Vertical Field Angle (10%)	62.6
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	375
Beam Efficiency	N.A.
Field Lumens	636
Field Efficiency	N.A.
Spill Lumens	97
Luminaire Lumens	733
Total Efficiency	N.A.
Total Luminaire Watts	8.3
Ballast Factor	1.00




IES FLOOD REPORT
PHOTOMETRIC FILENAME : COMH-12-L830.IES

AXIAL CANDELA


DEG.	HOR.	DEG.	VERT.
90	.45	90	.39
85	.38	85	.42
75	1.98	75	1.52
65	5.81	65	5.85
55	12.69	55	12.13
47.5	20.01	47.5	19.13
42.5	30.91	42.5	28.58
37.5	59.13	37.5	51.94
33	120.23	33	102.21
29	221.53	29	184.65
25.5	363.14	25.5	298.44
22.5	539.86	22.5	445.15
19.5	734.08	19.5	609.95
17	922.78	17	781.69
15	1073.74	15	919.08
13	1200.79	13	1046.44
11	1327.84	11	1173.81
9	1424.62	9	1285.23
7	1491.12	7	1380.72
5	1557.62	5	1476.2
3	1577.62	3	1528.76
1	1597.61	1	1581.33
0	1607.61	0	1607.61
-1	1597.61	-1	1633.23
-3	1577.62	-3	1684.48
-5	1557.62	-5	1735.73
-7	1491.12	-7	1703.65
-9	1424.62	-9	1671.57
-11	1327.84	-11	1596.84
-13	1200.79	-13	1479.46
-15	1073.74	-15	1362.08
-17	922.78	-17	1191.01
-19.5	734.08	-19.5	977.18
-22.5	539.86	-22.5	735.37
-25.5	363.14	-25.5	508.97
-29	221.53	-29	317.53
-33	120.23	-33	175.37
-37.5	59.13	-37.5	85.99
-42.5	30.91	-42.5	43.17
-47.5	20.01	-47.5	26.32
-55	12.69	-55	15.34
-65	5.81	-65	7.69
-75	1.98	-75	1.9
-85	.38	-85	.39
-90	.45	-90	.46

AXIAL CANDELA DISPLAY




Maximum Candela = 1735.73 Located At Horizontal Angle = 0, Vertical Angle = -5
Horizontal Axial Candela

AXIAL CANDELA DISPLAY



Maximum Candela = 1735.73 Located At Horizontal Angle = 0, Vertical Angle = -5
Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 1735.73 Located At Horizontal Angle = 0, Vertical Angle = -5
50% Maximum Candela = 867.865
10% Maximum Candela = 173.573