

UNIQUE

LIGHTING SYSTEMS®

IES FLOOD REPORT

PHOTOMETRIC FILENAME : PULS-12-L327.IES


DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 3408
[TESTLAB] Labsphere
[ISSUEDATE] 12/6/2019 6:24:50 AM
[MANUFAC] TORO
[LUMINAIRE] PULS-12-L327
[LAMP] LED-3W-CM6FL27K
[_AMBIENT] 22.4 deg C
[_POWERFACTOR] 0.5693
[_ATHD] 0.00%
[_CURRENT] 0.36
[_VOLTAGE] 11.96
[_Lumens] 200
[_END VOLTS] 12.06
[_END CURRENT] 0.34
[_END POWER] 2.38

Note: Candela values converted from Type-C to Type-B

CHARACTERISTICS

NEMA Type	4 H x 4 V
Maximum Candela	292.62
Maximum Candela Angle	0H -5V
Horizontal Beam Angle (50%)	39.0
Vertical Beam Angle (50%)	40.9
Horizontal Field Angle (10%)	69.5
Vertical Field Angle (10%)	69.4
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	82
Beam Efficiency	N.A.
Field Lumens	137
Field Efficiency	N.A.
Spill Lumens	13
Luminaire Lumens	150
Total Efficiency	N.A.
Total Luminaire Watts	2.42
Ballast Factor	1.00




IES FLOOD REPORT
PHOTOMETRIC FILENAME : PULS-12-L327.IES

AXIAL CANDELA


DEG.	HOR.	DEG.	VERT.
90	.1	90	.16
85	.1	85	.19
75	.18	75	.36
65	.35	65	.62
55	.76	55	1.71
47.5	3.04	47.5	7.15
42.5	8.43	42.5	15.59
37.5	21.38	37.5	29.28
33	40.25	33	48.47
29	63.35	29	71.57
25.5	93.06	25.5	93.96
22.5	118.18	22.5	117.6
19.5	143.95	19.5	142.68
17	168.47	17	165.9
15	188.08	15	184.48
13	205.26	13	201.05
11	222.45	11	217.62
9	238.59	9	233.31
7	253.7	7	248.12
5	268.81	5	262.92
3	275.73	3	272.19
1	282.64	1	281.46
0	286.1	0	286.1
-1	282.64	-1	287.4
-3	275.73	-3	290.01
-5	268.81	-5	292.62
-7	253.7	-7	284.68
-9	238.59	-9	276.74
-11	222.45	-11	265.35
-13	205.26	-13	250.5
-15	188.08	-15	235.65
-17	168.47	-17	210.92
-19.5	143.95	-19.5	180
-22.5	118.18	-22.5	135.57
-25.5	93.06	-25.5	91.84
-29	63.35	-29	53.52
-33	40.25	-33	19.65
-37.5	21.38	-37.5	2.69
-42.5	8.43	-42.5	.73
-47.5	3.04	-47.5	.3
-55	.76	-55	.1
-65	.35	-65	.1
-75	.18	-75	.06
-85	.1	-85	.06
-90	.1	-90	.06

AXIAL CANDELA DISPLAY



Maximum Candela = 292.62 Located At Horizontal Angle = 0, Vertical Angle = -5
H - Horizontal Axial Candela
V - Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 292.62 Located At Horizontal Angle = 0, Vertical Angle = -5
50% Maximum Candela = 146.31
10% Maximum Candela = 29.262