

# UNIQUE

## LIGHTING SYSTEMS®

### IES FLOOD REPORT

PHOTOMETRIC FILENAME : BIGB-12-L530.IES


### DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002  
[TEST] 3623  
[TESTLAB] Labsphere  
[ISSUEDATE] 2/19/2021 11:34:40 AM  
[MANUFAC] TORO  
[LUMINAIRE] BIGB-12-L530  
[LAMP] LED-5W-CPFL30K  
[ \_AMBIENT] 21.4 deg C  
[ \_POWERFACTOR] 0.5939  
[ \_ATHD] 0.00%  
[ \_CURRENT] 0.57  
[ \_VOLTAGE] 12.01  
[ \_Lumens] 283.93  
[ \_END VOLTS] 12.02  
[ \_END CURRENT] 0.56  
[ \_END POWER] 4.01

Note: Candela values converted from Type-C to Type-B

### CHARACTERISTICS

NEMA Type	4 H x 4 V
Maximum Candela	630.73
Maximum Candela Angle	0H 0V
Horizontal Beam Angle (50%)	34.2
Vertical Beam Angle (50%)	33.9
Horizontal Field Angle (10%)	69.5
Vertical Field Angle (10%)	68.9
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	123
Beam Efficiency	N.A.
Field Lumens	246
Field Efficiency	N.A.
Spill Lumens	39
Luminaire Lumens	285
Total Efficiency	N.A.
Total Luminaire Watts	4.07
Ballast Factor	1.00




**IES FLOOD REPORT**  
**PHOTOMETRIC FILENAME : BIGB-12-L530.IES**

**AXIAL CANDELA**


DEG.	HOR.	DEG.	VERT.
90	.17	90	.12
85	.12	85	.14
75	.12	75	.16
65	.11	65	.57
55	1.78	55	5.84
47.5	12.51	47.5	14.96
42.5	25.26	42.5	25.05
37.5	45.31	37.5	41.25
33	74.19	33	65.14
29	111.29	29	97
25.5	155.29	25.5	136.14
22.5	205.75	22.5	184.62
19.5	261.17	19.5	238.94
17	317.36	17	296.11
15	362.31	15	341.85
13	410.26	13	393.11
11	458.21	11	444.37
9	502.67	9	492.86
7	543.65	7	538.58
5	584.63	5	584.3
3	603.07	3	602.87
1	621.51	1	621.44
0	630.73	0	630.73
-1	621.51	-1	624.72
-3	603.07	-3	612.7
-5	584.63	-5	600.68
-7	543.65	-7	561.68
-9	502.67	-9	522.69
-11	458.21	-11	478.75
-13	410.26	-13	429.87
-15	362.31	-15	380.99
-17	317.36	-17	333.89
-19.5	261.17	-19.5	275.01
-22.5	205.75	-22.5	216.12
-25.5	155.29	-25.5	162.51
-29	111.29	-29	117.1
-33	74.19	-33	79.16
-37.5	45.31	-37.5	49.91
-42.5	25.26	-42.5	29.81
-47.5	12.51	-47.5	17.52
-55	1.78	-55	6.69
-65	.11	-65	.77
-75	.12	-75	.18
-85	.12	-85	.15
-90	.17	-90	.15

AXIAL CANDELA DISPLAY




Maximum Candela = 630.73 Located At Horizontal Angle = 0, Vertical Angle = 0  
Horizontal Axial Candela

AXIAL CANDELA DISPLAY



Maximum Candela = 630.73 Located At Horizontal Angle = 0, Vertical Angle = 0  
Vertical Axial Candela

ISOCANDELA CURVES



Maximum Candela = 630.73 Located At Horizontal Angle = 0, Vertical Angle = 0  
50% Maximum Candela = 315.365  
10% Maximum Candela = 63.073