


PROJECT: _____

MODELS: _____



150W, 300W & 600W LED Transformer LED Series

KEY FEATURES & BENEFITS

Long lasting low-voltage landscape lighting power supply

Cutting-edge core design significantly enhances electrical efficiency

Improved thermal management ensures years of reliable operation

Designed to meet stringent safety and performance standards for electrical equipment

Rated to UL-1838 (Landscape Lighting) and UL-379 (Pool & Spa)



SPECIFICATION

Model	150SSSL-LED-PS	300SSSL-LED-PS	600SSSL-LED-PS
-------	----------------	----------------	----------------


ELECTRICAL

Power Output (Watts)	150W	300W	600W
Power Input	120V AC, 60Hz		
Output Voltage	12V, 13V, 14V, 15V		
Transformer Volt Amps	180VA @ 12V 180VA @ 13V** 180VA @ 14V** 180VA @ 15V**	300VA @ 12V 325VA @ 13V 325VA @ 14V** 325VA @ 15V**	600VA @ 12V 650VA @ 13V 650VA @ 14V** 650VA @ 15V**
** VA is thermally regulated to prevent overload. Exceeding stated VA will shut down			
Secondary Electrical Protection	15-amp breaker	25-amp breaker	2X25-amp breaker


MECHANICAL

Dimensions	4.75"W x 14.25"H x 5.125"D		7.08"W x 14.75"H x 6.67"D
Weight	13.25 lbs.	15.5 lbs.	31.75 lbs.
Power Cord	16AWG with NEMA 5-15P Plug, 6' length		
Cabinet	304 stainless steel, complies with NEMA 3R		
Finish	Stainless Steel		


DIMENSIONS & FEATURES




- 1 - Photocell Receptacle, Jumper
- 2 - 25 Amps Breaker
- 3 - Lockable Latch
- 4 - Power Cord Strain Relief
- 5 - Terminal Block
- 6 - Power Cord Receptacle, Polarized, NEMA 5-15R



- 7 - Door Label/RUN Information Listing
- 8 - 1/2" Conduit Access, Small Plug Cap
- 9 - Power Cord Supply Strain Relief
- 10 - 3/4" Conduit Access, Medium Plug Cap
- 11 - Power Cord, 16 AWG with NEMA 5-15P Plug
- 12 - 1-1/4" Conduit Access, Large Plug Cap



- 1 - Photocell Receptacle, Jumper
- 2 - 25 Amps Breaker
- 3 - Lockable Latch
- 4 - Power Cord Strain Relief
- 5 - Terminal Block
- 6 - Power Cord Receptacle, Polarized, NEMA 5-15R



- 7 - Door Label/RUN Information Listing
- 8 - 1/2" Conduit Access, Small Plug Cap
- 9 - Power Cord Supply Strain Relief
- 10 - 3/4" Conduit Access, Medium Plug Cap
- 11 - Power Cord, 16 AWG with NEMA 5-15P Plug
- 12 - 1-1/4" Conduit Access, Large Plug Cap

ACCESSORIES



LPCU-A

Digital Switch & Calendar Function



SMRT-T

Internet Gateway & App Control



T

Manual Timer



SNPC2

Snap in Photocell



CONFORMS TO
UL STD. UL838 /UL379
CERTIFIED TO
CSASTD.
C22.2 NO.218.1



We reserve the right to improve our products and make changes in the specifications and designs without notice and without incurring obligation. Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in design and features.

www.uniquelighting.com

5825 Jasmine Street, Riverside, CA 92504-1183 • Customer Service 800-995-4831 • Order Services - 800-862-1882

UNIQUE
LIGHTING SYSTEMS®

© ULS 03/25 Form No 25-0105-ULS-NA