



## Material Safety Data Sheet

Lawn-Boy, Inc.  
8111 Lyndale Ave S  
Bloomington, MN 55420

Revision Date: August 24, 2009

Issue Date: September 1, 2009

### Product Identification

<b>Product Name:</b>	Fuel Conditioner	<b>Parts Number:</b> 89875
<b>Product type:</b>	Fuel detergent, stabilizer and rust inhibitor	
<b>MSDS #</b>		
<b>Emergency Contact:</b>	Chemtrec : 1-800-424-9300	
<b>Contact Number:</b>	1-952-888-8801	

### Chemical Components

Chemical	CAS #	%	ACGIH TLV	OSHA PEL	Other
Isopropanol	67-63-0	95		PEL 400 ppm PEL 980 mg/m3	
Proprietary Additive	none	5			

### Physical and Chemical Properties

Characteristics	Physical Properties	Hazards Description	Physical Dangers																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td><b>Physical State</b></td> <td>liquid</td> </tr> <tr> <td><b>Color</b></td> <td>Amb er</td> </tr> <tr> <td><b>Odor</b></td> <td>solve nt odor</td> </tr> </table>	<b>Physical State</b>	liquid	<b>Color</b>	Amb er	<b>Odor</b>	solve nt odor	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Vapor pressure</td> <td>(MM HG): 97.0</td> </tr> <tr> <td>pH</td> <td>N/A</td> </tr> <tr> <td>Boiling point/range:</td> <td>180 F. (82.2 C)</td> </tr> <tr> <td>Melting point/range:</td> <td>N/A</td> </tr> <tr> <td>Specific gravity</td> <td>0.787</td> </tr> <tr> <td>Vapor density</td> <td>GT 1.0</td> </tr> <tr> <td>Evaporation rate</td> <td>N/A</td> </tr> <tr> <td>Solubility in water</td> <td>Soluble</td> </tr> <tr> <td>VOC content:</td> <td></td> </tr> <tr> <td>Flash Point</td> <td></td> </tr> <tr> <td colspan="2">Viscosity: N/A Decomposition Temperature: N/A Molecular Formula: N/A Molecular Weight: N/A</td> </tr> </table>	Vapor pressure	(MM HG): 97.0	pH	N/A	Boiling point/range:	180 F. (82.2 C)	Melting point/range:	N/A	Specific gravity	0.787	Vapor density	GT 1.0	Evaporation rate	N/A	Solubility in water	Soluble	VOC content:		Flash Point		Viscosity: N/A Decomposition Temperature: N/A Molecular Formula: N/A Molecular Weight: N/A		VOC Coating (minus water): 0 Lbs/Gallon Coating Density : 0 Lbs/Gallon Solvent Density : 0 Lbs/Gallon Percent Solvent (volume): 0 Percent Solids (volume): 0 Percent Water (volume): 0 Percent Volatile by Weight: 0 Miscellaneous: % Volatile/Volume: 100.0 Specific Gravity (H2O = 1): N/A Percent Solvent (Volume): N/A Percent Solids (Volume): N/A Percent Water (Volume): N/A	Product is flammable, keep away from sources of ignition, combustibles, oxidizing material and acid.  Chemical Stability: Stable: Yes Conditions to Avoid: Incompatibilities with Other Materials: Strong oxidizing agents, amines, chlorinated compounds and caustic materials. Hazardous Decomposition Products: Excessive heating and/or incomplete combustion will produce carbon monoxide. Hazardous Polymerization: Hazardous Polymerization May Occur: No
<b>Physical State</b>	liquid																														
<b>Color</b>	Amb er																														
<b>Odor</b>	solve nt odor																														
Vapor pressure	(MM HG): 97.0																														
pH	N/A																														
Boiling point/range:	180 F. (82.2 C)																														
Melting point/range:	N/A																														
Specific gravity	0.787																														
Vapor density	GT 1.0																														
Evaporation rate	N/A																														
Solubility in water	Soluble																														
VOC content:																															
Flash Point																															
Viscosity: N/A Decomposition Temperature: N/A Molecular Formula: N/A Molecular Weight: N/A																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2"><b>HMIS Rating</b></td> </tr> <tr> <td><b>Health:</b></td> <td>2</td> </tr> <tr> <td><b>Flammability:</b></td> <td>3</td> </tr> <tr> <td><b>Physical Hazard:</b></td> <td>0</td> </tr> </table>	<b>HMIS Rating</b>		<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Physical Hazard:</b>	0																							
<b>HMIS Rating</b>																															
<b>Health:</b>	2																														
<b>Flammability:</b>	3																														
<b>Physical Hazard:</b>	0																														

## Health Hazards

Major Routes of Exposure:		Ingredients Considered Hazardous to Health	Potential Health Effects:
Inhalation	X	This product does not contain any components above de minimus concentrations that are considered carcinogenic by OSHA, IARC or NTP.	<b>Inhalation.</b> Narcotic chemical affecting central nervous system resulting in: dizziness, nausea, visual impairment, narcosis and muscular impairment.
Skin	X		<b>Skin contact</b> Prolonged or repeated skin contact may cause dermatitis, scaling and possible systemic effects.
Ingestion	X		<b>Eye contact:</b> Irritant
Eye	X		<b>Ingestion:</b> Low level of toxicity, small amounts of liquid aspirated into the respiratory system during ingestion may cause pulmonary edema.

First Aid Measures	Personal Protection
<p><b>Eye:</b> If the product contacts the eyes, immediately wash the eyes with large quantities of room temperature water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. A follow up visit to an ophthalmologist should be made. Contact lenses should not be worn when working with this chemical.</p> <p><b>Skin:</b> If the product contacts the skin, promptly wash the contaminated skin with soap and water for at least 15 minutes. If this product penetrates the clothing, promptly remove the clothing and wash the skin with soap and water. Systemic effects may be delayed 18 to 72 hours, therefore keep individual under observation.</p> <p><b>Ingestion:</b> If this product is ingested. DO NOT INDUCE A PERSON TO VOMIT. Get medical attention immediately.</p> <p><b>Inhalation:</b> Move the exposed person to fresh air at once and call emergency medical care. If breathing has stopped, give artificial respiration. If breathing is difficult, give humidified oxygen.</p> <p><b>Notes to Physician:</b> No data available.</p>	<p><b>GENERAL HYGIENE CONSIDERATIONS:</b> Use normal hygiene practices.</p> <p><b>OTHER PRECAUTIONS:</b> Product is flammable, handle accordingly.</p> <p><b>ENGINEERING CONTROLS:</b>            Local Exhaust: Provide local ventilation to maintain exposure levels below recommended exposure limits.            Mechanical (General): In confined spaces, mechanical ventilation may be required.            Special Ventilation: N/A            Other Ventilation: N/A</p> <p><b>PERSONAL PROTECTIVE EQUIPMENT</b>  <b>Eyes/face:</b> Use splash proof chemical, safety goggles or appropriate full-face respirator. Contact lenses should not be worn when working with this chemical.  <b>Skin:</b> Use natural rubber or neoprene gloves as required.  <b>Respirators:</b> Do not use air purifying respirator. Use NIOSH approved respirator approved supplied or self contained respirator. Respirators must be selected based on the airborne levels found in the workplace and must not exceed the working limits of the respirator.  <b>Other Protective Clothing/Equipment:</b>            If there is a possibility of exposure of an individual's body to the product, wear body covering work clothes to avoid prolonged or repeated exposure.</p>

## Fire and Explosion Hazards

Extinguishing Media	Special Fire Fighting Procedures	Unusual Fire and Explosion Hazards
Use halon replacement or carbon dioxide extinguishers or alcohol foam for small fires. Water spray or fog can cool fire but may not be effective in extinguishing fire. Large fires should be extinguished with alcohol foam. Use water spray to cool containers exposed to fire. Containers may explode in heat or fire.	Flash Point: 54 F. (12.2 C.) TOC Autolgnition Temperature: N/A Flammable Limits Lower Limit: Explosive Limit (LEL):2.0 Upper Limit: Explosive Limit (UEL): 12.0 Wear NIOSH approved SCBA respirator in the positive pressure mode and chemical protective clothing. Flammable Limits: 2.0 to 12.0	Dangerous fire and explosion hazard when exposed to heat or flame. Isopropanol is extremely flammable and forms explosive mixtures with air. Isopropanol vapors may travel considerable distance to a source of ignition and flash back.

## Handling and Storage

Accidental Release /Spill Measures to Take	Precautions for Storage	Handling
Small Spill: Remove sources of heat or ignition, provide adequate ventilation, contain leak using absorbent, inert, non-combustible material. Large Spill: Contain spill, transfer to secure containers. In the event of an uncontrolled material release, the user should determine if release is reportable under applicable laws and regulations.	Store in an area equipped with automatic sprinklers or fire extinguishing system. Empty containers contain product residues, assume empty container to have the same hazards as full containers. Store in a well ventilated place away from sources of ignition, combustibles, oxidizing materials and acid.	

## Disposal/Transportation

Disposal Method	Transportation
Dispose of product in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of MSDS for hazard warning information.	Transportation Information: Shipping Information (CFR 49 and IMDG): Proper Shipping Name: Additive, gasoline DOT Hazard Class: Consumer commodity, ORM-D DOT UN Number: None required. IMDG Shipping Name: Not an exported item. Label Information: No data available.

## Regulations

SARA Title III: Section 302: None Section 304: None Section 311: Hazard categories-Fire Hazard-Yes; Acute=Yes and Chronic=Yes Section 313: None CERCLA: Section 311(b)(4): Requires discharges of crude oil and petroleum products in any kind or form to waters must immediately be reported to the National Response Center at (800) 424-8802.
--

## Toxicology Information

No data available.
--------------------

## Ecological Information

No data available.
--------------------