

21" COMMERCIAL HEAVY DUTY MOWERS	21" COMMERCIAL HEAVY DUTY MOWERS					
	22289	22290	22297	22298	22295	22296
ENGINE*	Toro® OHV 159cc	» Kawasaki® ZS FJ180V	» Kawasaki ZS FJ180V KAI	Kawasaki BBC FJ180V KAI	» Honda® ZS GXV160	Honda BBC GXV160
STARTER	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil
TIRES	9" x 2" Rubber tires	9" x 2" Rubber tires	9" x 2" Rubber tires	9" x 2" Rubber tires	9" x 2" Rubber tires	9" x 2" Rubber tires
FUEL CAPACITY	0.5 gallon	0.5 gallon	» 1 gallon	1 gallon	1 gallon	1 gallon
TRANSMISSION	Push	Self Propel Variable Speed RWD	» Self Propel 3-Speed RWD	Self Propel 3-Speed RWD	Self Propel 3-Speed RWD	Self Propel 3-Speed RWD
MAXIMUM GROUND SPEED	N/A	4.2 mph	4.2 mph	4.2 mph	4.2 mph	4.2 mph
WEIGHT	92 lbs.	112 lbs.	120 lbs.	124 lbs.	117 lbs.	121 lbs.
DECK WIDTH	21"	21"	21"	21"	21"	21"
DECK TYPE	Recycler® Cutting System / Rear Bag	Recycler® Cutting System / Rear Bag	Recycler Cutting System / Rear Bag	Recycler Cutting System / Rear Bag	Recycler Cutting System / Rear Bag	Recycler Cutting System / Rear Bag
DECK CONSTRUCTION	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy
CUTTING HEIGHT	1.0" - 4.5"	1.0" - 4.5"	1.0" - 4.5"	1.0" - 4.5"	1.0" - 4.5"	1.0" - 4.5"
BLADES	0.135" steel w/blade stiffener	0.135" steel w/blade stiffener	0.135" steel w/blade stiffener	0.135" steel w/blade stiffener	0.135" steel w/blade stiffener	0.135" steel w/blade stiffener
BLADE ENGAGEMENT	Zone Start	Zone Start	Zone Start	» BBC	Zone Start	» BBC
CONTROL SYSTEM	Single Bail	2-Bail	Single Bail	Dual-Action Single Bail	Single Bail	Dual-Action Single Bail
STEEL DECK WEAR PLATES	N/A	N/A	Standard	Standard	Standard	Standard
ENGINE GUARD	N/A	N/A	Standard	Standard	Standard	Standard

» = Enhanced or Step-up feature



COMMERCIAL GRADE WHEELS

Tough co-polymer wheels feature precision ball bearings for long life, less downtime, and lower replacement costs. These large 9" x 2" wheels also provide a light footprint that is easy on turf.



EASY EMPTY BAG

The large bag features an easy-empty design, making quick work of clipping disposal.



4 POINT HEIGHT OF CUT

The robust design provides maximum life and durability. Front spring arms are contained within the wheels for ultimate protection. Cut in more conditions with heights ranging from 1" to 4.5".



REAR BAGGING SYSTEM

The wide opening and ramped profile of the tunnel maximize bag fill.



STEEL DECK WEAR PLATE

Extend the life of your mower deck with replaceable steel wear plates that protect against bottom and side impacts.
Select models.