


COMMERCIAL 3000 SERIES	Z MASTER® COMMERCIAL 3000 SERIES				
	74952	74955 / 78953 CARB Model	74950	74958	74959
ENGINE* AT 3600 RPM	20.5 hp Kawasaki® FX 726cc	25 hp Kohler® Command Pro 747cc	25.5 hp Kawasaki FX 852cc	25 hp Kohler Command Pro EFI 747cc	25 hp Kohler Command Pro 747cc
ELECTRIC START			Standard		
HEAVY-DUTY CANISTER AIR CLEANER			Standard		
DRIVE TIRES	23" x 9.5" - 12"		24" x 12" x 12"		
CASTER TIRES	13" x 5" - 6" Pneumatic		13" x 6.5" - 6" Pneumatic		
FUEL CAPACITY			8 gallons		
DIGITAL FUEL GAUGE			Standard		
DIGITAL HOUR METER			Standard		
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps & wheel motors		Unitized 12 cc pumps & wheel motors with cooling fans		
MAX GROUND SPEED (FWD)	8.5 mph		10 mph		
SEAT			Premium Bolstered		
DECK WIDTH	48"	52"	60"	60"	72"
CUTTING DECK			TURBO FORCE®		
DECK DEPTH			5.5"		
DECK CONSTRUCTION			7-gauge high-strength steel		
BULL-NOSE BUMPER			Standard		
ADJUSTABLE DISCHARGE BAFFLE			Standard		
RUBBER DISCHARGE CHUTE			Standard		
1" HEAVY-DUTY SPINDLE SHAFT			Standard		
SPINDLE BEARINGS			Greaseable Ball Bearings		
DECK LIFT ASSIST PEDAL			Standard		
CUTTING HEIGHT			1.0" - 5.5" in .25" increments		




COMMERCIAL ENGINES

Powerful Kawasaki FX & Kohler commercial-grade engines provide professional quality performance. Heavy-duty canister air filtration system protects engine from contaminants and prolongs product life.



TOUGH SPINDLE ASSEMBLIES

Toro's rugged cast-iron spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.



SMOOTH, POWERFUL RESPONSE

The unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



490-9333 ©2016 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See retailer for warranty details.