

<b>Z MASTER<sup>®</sup></b> WITH MyRIDE™ SUSPENSION SYSTEM	<b>74994</b> COMMERCIAL 3000 SERIES	<b>74996</b> COMMERCIAL 3000 SERIES	<b>74995</b> PROFESSIONAL 5000 SERIES	<b>74991</b> PROFESSIONAL 5000 SERIES	<b>74997</b> PROFESSIONAL 6000 SERIES	<b>74998</b> PROFESSIONAL 6000 SERIES
ENGINE*	25 hp Kohler® Command Pro 747cc	25.5 hp Kawasaki® FX 726cc	25 hp Kohler Command Pro EFI 747cc	25 hp Kohler Command Pro EFI 747cc	31 hp Kawasaki FX 921cc	31 hp Kawasaki FX 921cc
HEAVY-DUTY CANISTER AIR CLEANER	Standard					
DRIVE TIRES	23" x 9" X 12"			24" x 12" x 12"		
CASTER TIRES	13" x 6.5" - 6" Pneumatic			13" x 6.5" - 6" Semi-pneumatic		
FUEL CAPACITY	8 gallons , single-point fill			12 gallons, single-point fill		
DIGITAL HOUR METER	Standard					
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and 14.6 cubic inch wheel motors				Unitized 16 cc pumps and 17.1 cubic inch wheel motors	
MAX GROUND SPEED (FWD)	8.5 mph		10 mph		11.5 mph	
<b>MyRIDE SUSPENSION SYSTEM</b>						
COMFORT PLATFORM	MyRIDE Suspension System					
PLATFORM TRAVEL	3.6"					
SHOCKS	1 Front / 2 Rear					
ISO MOUNTS	Qty 4, 2.5" 3-D isolation mounts					
SEAT	Deluxe seat with padded armrests					
ADJUSTABILITY	5 point adjustment on rear shocks					
DECK WIDTH	52"	60"	52"	60"	60"	72"
CUTTING DECK	TURBO FORCE®					
DECK DEPTH	5.5"					
DECK CONSTRUCTION	7-gauge high-strength steel					
BULL-NOSE BUMPER	Standard					
ADJUSTABLE DISCHARGE BAFFLE	Standard			Standard, tools-free		
RUBBER DISCHARGE CHUTE	Standard					
1" HEAVY-DUTY SPINDLE SHAFT	Standard					
SPINDLE BEARINGS	Greaseable ball bearings					Tapered roller bearings
DECK LIFT ASSIST PEDAL	Standard					
CUTTING HEIGHT	1.0" - 5.5" in .25" increments					